
Peplink Balance One

Gigabit Dual-WAN Router with Dual-Band 11n Wi-Fi





1 Gbps

Router Throughput

Dual-Band 11n Wi-Fi

2.4GHz & 5GHz

SpeedFusion[™]

Bonding Technology

Unbreakable VPN



Also supports InControl 2 cloud management. Learn more at peplink.com/incontrol-2/

One Huge Leap Forward for SMB, and Branch Networking.

The Balance One gigabit router with dual-WAN load balancing delivers big-business uptime and speed in an affordable package designed just for SMBs, branch offices, and power users. Featuring simultaneous dual-band 802.11n Wi-Fi, eight GbE LAN ports, and exclusives like our built-in AP Controller, captive portals, and InControl 2 cloud management, it's the one router you need for enterprise-grade networking in smaller environments.

Gigabit Performance. Uptime, All the Time.

The Balance One dual-WAN router drives data at 1Gbps and keeps connections dependable and fast with automatic balancing and failover between links. Connect up to two fiber, 4G LTE/3G cellular, or other links in any combination for 24/7 connectivity and lightning-quick performance.

Superfast Dual-Band Wi-Fi. Eight GbE LAN Ports.

With simultaneous 2.4 and 5Ghz 802.11n Wi-Fi and eight gigabit Ethernet LAN ports onboard, the Peplink Balance One makes it easy to connect all your devices at high speeds, without complicated setup, compromises, or external switches to buy and maintain.

Unparalleled Modem Support. *


The Balance One's USB port supports more than 200 4G LTE/3G modems used by a variety of carriers worldwide. Whatever you're using, it'll probably work without a hitch.

Built-in AP Controller and Captive Portals. Easy Management Anywhere.


AP Controller puts you in charge of all connected access points using an intuitive built-in management console. You can also create and manage custom captive portals using your Balance One. And you can do it all from anywhere using InControl 2 cloud management.

* USB modem support requires a future firmware scheduled to be released in March, 2014

Access Company Resources from Home Using SpeedFusion Unbreakable VPN



Setup, Manage, and Monitor Office Wi-Fi from Your Balance One



Connect Your Smart Home with Gigabit Fiber Internet (FTTH) and LTE Backup for 100% Uptime



Create Guest Hotspots Complete with Captive Portals

AP One



Specifications

Balance One		
WAN Interface	2x 10/100/1000M Ethernet Ports 1x USB Interface	
LAN Interface	8x 10/100/1000M Ethernet Ports	
Wi-Fi Interface	Simultaneous Dual-Band 802.11a/b/g/n Access Point	
Wi-Fi AP Operating Frequency	2412 – 2472 and 5180 - 5825 MHz	
Router Throughput	1Gbps	
Number of SpeedFusion Pe	eers 2	
PepVPN/SpeedFusion Throughput	30Mbps	
Power Input	Device: 12V – 24V DC AC Adapter: AC Input 100V – 240V, DC Output 12V	
Power Consumption	15W (max.)	
Dimension	6.3 x 10.7 x 1.2 inches 160 x 271 x 30 mm (L x W x H)	
Weight	1.3 pound 570 grams	
Operating Temperature	-40° – 149°F -40° – 65°C	
Humidity	15% – 95% (non-condensing)	
Certifications	FCC, CE, RoHS	







For the most updated specifications, please refer to our website: http://www.peplink.com/balance-one/.

Features

Warranty

WAN

USB 4G/3G Modem Support * Support for PPPoE, Static IP, DHCP Support for Dynamic DNS services WAN Link Health Check Intelligent Failover Bandwidth Allowance Monitor

LAN

DHCP Server for LAN Clients Extended DHCP Options **DHCP** Reservation DNS Proxy for LAN Clients

Complete VPN Solution

1-Year Limited Warranty

PepVPN/SpeedFusion ^ Site-to-Site VPN Bandwidth Aggregation ^ Hot Failover ^ 256-bit AES Encryption Pre-shared Key Authentication **Dvnamic Routing** PPTP VPN Server RADIUS, LDAP Authentication IPsec VPN (Network-to-Network)

Load Balancing

Intelligent Failover Session Persistence Per-Service Load Distribution Multiple Algorithms

 * Requires a future firmware scheduled to be released in March, 2014 $^{\wedge}$ SpeedFusion is available on BPL-ONE-SF

Networking

NAT and IP Forwarding Static Routes Port Forwarding Many to One, One to One NAT NAT Pool SIP ALG, H.323 ALG UPnP. NAT-PMP WINS Server

Works With

verizon

Security

Stateful Firewall DoS Prevention

Advanced OoS

User Groups Bandwidth Reservation Individual Bandwidth Limit Application Prioritization By User Groups SIP, HTTPS, VPN QoS Custom Application QoS

And 200+ USB Modem from Worldwide Carriers

Device Management

Web Administrative Interface Command Line Interface InControl Cloud Management **Email Notification** Active Client & Session Lists **Bandwidth Usage Statistics** Syslog Service SNMP v1, v2c and v3

Certification

FCC, CE, RoHS

at&t Sprint 🎾 T - Mobile - Lte

Product Ordering Information

Balance One

Product Code	Description
BPL-ONE	Gigabit dual-WAN router with dual-band 11n Wi-Fi and 8-port GbE switch. Supports PepVPN, InControl Cloud Management, and built-in AP Controller with captive portal.
BPL-ONE-3Y	Gigabit dual-WAN router with dual-band 11n Wi-Fi and 8-port GbE switch. Supports PepVPN, InControl Cloud Management, and built-in AP Controller with captive portal. Includes 3 years of InControl Cloud Management service and 3 years of standard warranty.
BPL-ONE-SF	Gigabit dual-WAN router with dual-band 11n Wi-Fi and 8-port GbE switch. Supports PepVPN, InControl Cloud Management, and built-in AP Controller with captive portal. Supports SpeedFusion bandwidth bonding.



United States T: +1 (650) 450 9669 E: sales@peplink.com

www.peplink.com